

Through bolt S-KA 10/30 ZP

SORMAT CODE 9640001136

Premium-quality through bolts for fixing in non-cracked and cracked concrete

- Torque-controlled expansion anchors for pre-, push-through and distance installations.
- When torque is applied the expansion clip expands developing frictional grip with the drill hole walls.
- Anchor diameter and max. fixture thickness marked on the body.
- The use of S-KA setting tool makes serial installation safer and quicker.
- ZP for dry indoor and temporary outdoor use.

APPLICATIONS

- Steel structures
- Column base plates
- Seatings
- Barriers
- Cable racks
- Handrails
- Ladders
- Façade systems

APPROVALS / CERTIFICATES



ETA-08/0173 + DoPs



0809-CPR-1078



Seismic resistance (ETA-08/0173)



TC 6236-21



Fire resistance (ETA-08/0173)

PRODUCT OVERVIEW

Other codes	SNRO 1356626 / LVI 3253028
Material	Steel, zinc plated
Packages	box (bag): 25 / outer carton: 125 / pallet: 7000
Weight	69.6 kg / 1000

BASE MATERIALS

APPROVED FOR

- Cracked concrete
- Non-cracked concrete

ALSO SUITABLE FOR

- Natural stone

Technical data

INSTALLATION DETAILS

Size
Length (L)
Thread (f)
Width across flats (SW)
Max. fixture thickness (T_{fix})



INSTALLATION DETAILS

M10	Hole in fixture (D _f)	12
112	Drill hole diameter (d ₀) ∅	10
67	Minimum drill hole depth	75
17	Drill hole depth (h ₁)	75
30	Nominal setting depth (H _{nom})	68
	Effective setting depth (H _{ef})	60
	Installation torque (T _{inst})	35

Performance data

Base material	Load type	Embedment depth (h_{nom})	Load direction	Load value
All				
Non-cracked concrete C20/25	N_{Rec}	68 mm		6.3 kN
Non-cracked concrete C20/25	V_{Rec}	68 mm		10.3 kN
Cracked concrete C20/25	N_{Rec}	68 mm		3.6 kN
Cracked concrete C20/25	V_{Rec}	68 mm		10.3 kN

Installation

