

Through bolt S-KA+ 10/50/30 ZP

SORMAT CODE 9640001327



Improved premium-quality through bolts for fixing in non-cracked and cracked concrete

- Torque-controlled expansion anchors for pre-, push-through and distance installations.
- When torque is applied the expansion clip expands developing frictional grip with the drill hole walls.
- Anchor diameter and max. fixture thicknesses marked on the body. Anchor length letter code marked on the bolt head.
- M8, M10 and M12 have two different anchorage depths.
- The use of S-KA setting tool makes serial installation safer and quicker.
- Seismic performance category C1/C2 ($h_{ef, std}$).
- ZP for dry indoor use.

PRODUCT OVERVIEW

Other codes	SNRO 1324081 / LVI 3253670
Material	Steel, zinc plated
Packages	box (bag): 25 / outer carton: 125 / pallet: 7000
Weight	68.9 kg / 1000
GTIN-13	6416031013270

APPLICATIONS

- Steel structures
- Column base plates
- Seatings
- Barriers
- Cable racks
- Handrails
- Ladders
- Façade systems

BASE MATERIALS

APPROVED FOR

- Cracked concrete
- Non-cracked concrete

ALSO SUITABLE FOR

- Natural stone

APPROVALS / CERTIFICATES



ETA-16/0934 + DoPs



Fire resistance (ETA-16/0934)



0809-CPR-1252




Seismic resistance (ETA-16/0934)

Technical data

INSTALLATION DETAILS









Size	M10
Length (L)	112
Thread (f)	67
Width across flats (SW)	17
Max. fixture thickness (T _{fix})	50/30



INSTALLATION DETAILS

Hole in fixture (D _f)	12
Drill hole diameter (d ₀) ∅	10
Minimum drill hole depth	55/75
Drill hole depth (h ₁)	55/75
Nominal setting depth (H _{nom})	48/68
Effective setting depth (H _{ef})	40/60
Installation torque (T _{inst})	30

Performance data

Base material	Load type	Embedment depth (h_{nom})	Load direction	Load value
All				
Non-cracked concrete C20/25	N_{Rec}	48 mm		5.7 kN
Non-cracked concrete C20/25	V_{Rec}	48 mm		11.7 kN
Non-cracked concrete C20/25	N_{Rec}	68 mm		9.0 kN
Non-cracked concrete C20/25	V_{Rec}	68 mm		11.7 kN
Cracked concrete C20/25	N_{Rec}	48 mm		4.1 kN
Cracked concrete C20/25	V_{Rec}	48 mm		11.7 kN
Cracked concrete C20/25	N_{Rec}	68 mm		5.7 kN
Cracked concrete C20/25	V_{Rec}	68 mm		11.7 kN

Installation

