

Through bolt S-KAH 16/20 A4

SORMAT CODE 9640005171

Premium-quality through bolts for fixing in non-cracked and cracked concrete

- Torque-controlled expansion anchors for pre-, push-through and distance installations.
- When torque is applied the expansion clip expands developing frictional grip with the drill hole walls.
- Anchor diameter and max. fixture thickness marked on the body.
- The use of S-KA setting tool makes serial installation safer and quicker.
- A4 for indoor, outdoor and industrial use.

APPLICATIONS

- Steel structures
- Column base plates
- Seatings
- Barriers
- Cable racks
- Handrails
- Ladders
- Façade systems

APPROVALS / CERTIFICATES



ETA-08/0173 + DoPs



0809-CPR-1078



Seismic resistance (ETA-08/0173)



TC 6236-21



Fire resistance (ETA-08/0173)

PRODUCT OVERVIEW

Other codes	SNRO 1356851 /
Material	Stainless steel, A4
Packages	box (bag): 10 / outer carton: 50 / pallet: 2800
Weight	219.2 kg / 1000

BASE MATERIALS

APPROVED FOR

- Cracked concrete
- Non-cracked concrete

ALSO SUITABLE FOR

- Natural stone

Technical data

INSTALLATION DETAILS

Size
Length (L)
Thread (f)
Width across flats (SW)
Max. fixture thickness (T_{fix})



INSTALLATION DETAILS

M16	Hole in fixture (D _f)	18
138	Drill hole diameter (d ₀) ∅	16
80	Minimum drill hole depth	110
24	Drill hole depth (h ₁)	110
20	Nominal setting depth (H _{nom})	96
	Effective setting depth (H _{ef})	85
	Installation torque (T _{inst})	120

Performance data

Base material	Load type	Embedment depth (h_{nom})	Load direction	Load value
All				
Non-cracked concrete C20/25	N_{Rec}	96 mm		16.7 kN
Non-cracked concrete C20/25	V_{Rec}	96 mm		26.9 kN
Cracked concrete C20/25	N_{Rec}	96 mm		9.5 kN
Cracked concrete C20/25	V_{Rec}	96 mm		25.7 kN

Installation

