

Pendulum arm KH 110/145

SORMAT CODE 9640060462



Unique solution for preventing thermal bridging in thick-plastering insulation systems

- MERK low-energy fixing is used in thick-plastering insulation systems to improve the energy efficiency of thick-plastering insulation systems and reduce the possibility of insulation system sagging.
- MERK combines in an innovative way the strengths of metal and plastic.
- Installation-ready MERK- bracket kit includes MERK- bracket made of reinforced plastic, a triangle-lock and a locking pin.
- KH- pendulum arms are available for insulation thicknesses from 50 mm to 270 mm (KH50-KH270) on request. Arms for over 150 mm insulation thicknesses are equipped with a possibility for temporary locking of the insulation layer.
- Screw kits for anchoring MERK- brackets for various bases are available on request.
- MERK metal components are manufactured from A2 stainless steel.

PRODUCT OVERVIEW

| | |
|--------------------|---------------------|
| Other codes | / |
| Material | Stainless Steel, A2 |
| Packages | box (bag): 100 |
| Weight | 14.0 kg / 1000 |

APPLICATIONS

- Facade renovations

BASE MATERIALS

ALSO SUITABLE FOR

- Aerated concrete block
- Hollow light expanded clay aggregate block
- Non-cracked concrete
- Perforated clay brick
- Solid clay brick
- Solid light expanded clay aggregate block
- Timber-based building boards

Technical data

INSTALLATION DETAILS

Insulation thickness 110

