

Concrete Screw S-CSA HEX 6X120/65/80 SW13 ZP

SORMAT CODE 9640071319

ETA-approved 6/8/10 concrete screw for cracked and non-cracked concrete

- Self-tapping, approved screw anchors for push-through installations.
- Requires a small drill hole diameter. No prescribed tightening torque.
- No expansion forces allowing for small edge distances and spacings.
- Fully removable.
- ZP for dry indoor use.

APPLICATIONS

- Facade scaffoldings
- Temporary fixings
- Seatings
- Shelves
- Cable racks
- Handrails
- Battens

APPROVALS / CERTIFICATES



ETA-16/0945 + DoPs



TC 5905-19



0809-CPR-1238



ETA-17/1009 + DoPs



0809-CPR-1202



Fire resistance (ETA-16/0945)

PRODUCT OVERVIEW

Other codes	SNRO 1310874 /
Material	Steel, zinc plated
Packages	box (bag): 50 / outer carton: 250 / pallet: 14000
Weight	33.1 kg / 1000

BASE MATERIALS

APPROVED FOR

- Cracked concrete
- Hollow-core slab
- Non-cracked concrete

ALSO SUITABLE FOR


- Solid clay brick
- Solid sand-lime brick



Technical data

INSTALLATION DETAILS

Size	6
Length (L)	120
Width across flats (SW)	13
Drive	T30
Max. fixture thickness (T _{fix})	65/80



INSTALLATION DETAILS

Hole in fixture (D _f)	9
Drill hole diameter (d ₀) ∅	6
Minimum drill hole depth	65/50
Drill hole depth (h ₁)	65/50
Nominal setting depth (H _{nom})	55/40
Installation torque (T _{inst})	14

HEAD DETAILS

Head diameter ∅	16,5
-----------------	------

Performance data

Base material All	ETA	Load type	Embedment depth (h_{nom})	Load direction	Load value
Non-cracked concrete C20/25	Yes	N_{Rec}	55 mm		4.5 kN
Non-cracked concrete C20/25	Yes	V_{Rec}	55 mm		5.6 kN
Cracked concrete C20/25	Yes	N_{Rec}	55 mm		2.1 kN
Cracked concrete C20/25	Yes	V_{Rec}	55 mm		4.5 kN
Non-cracked concrete C20/25	Yes	N_{Rec}	40 mm		1.7 kN
Non-cracked concrete C20/25	Yes	V_{Rk}	40 mm		5.4 kN
Cracked concrete C20/25	Yes	N_{Rec}	40 mm		1.7 kN
Cracked concrete C20/25	Yes	V_{Rec}	40 mm		5.4 kN
Hollow-core slab, bottom flange thickness 25 mm	Yes	N_{Rec}	40 mm		1.2 kN
Hollow-core slab, bottom flange thickness 25 mm	Yes	V_{Rec}	40 mm		1.2 kN

Installation

