

Concrete Screw S-CSA I 6X35 M8/M10X30 ZP

SORMAT CODE 9640071513



ETA-approved 6 concrete screw for cracked and non-cracked concrete

- Self-tapping, approved screw anchors for push-through installations.
- Requires a small drill hole diameter. No prescribed tightening torque.
- No expansion forces allowing for small edge distances and spacings.
- Fully removable.
- ZP for dry indoor use.

APPLICATIONS

- Pipe supports
- Installation channels

PRODUCT OVERVIEW

Other codes	SNRO 1324007 / LVI 3255598
Material	Steel, zinc plated
Packages	box (bag): 50 / outer carton: 250 / pallet: 14000
Weight	32.7 kg / 1000

BASE MATERIALS

- APPROVED FOR
- Cracked concrete
 - Hollow-core slab
 - Non-cracked concrete
- ALSO SUITABLE FOR
- Solid clay brick
 - Solid sand-lime brick

APPROVALS / CERTIFICATES



ETA-17/1009 + DoPs



0809-CPR-1238



TC 5905-19



Fire resistance (ETA-17/1009)

Technical data

INSTALLATION DETAILS

Size	6	Hole in fixture (D _f)	9
------	---	-----------------------------------	---

INSTALLATION DETAILS

Performance data

Base material	ETA	Load type	Embedment depth (h _{nom})	Load direction	Load value
All					
Non-cracked concrete C20/25	Yes	N _{Rec}	35 mm		1.4 kN
Non-cracked concrete C20/25	Yes	V _{Rec}	35 mm		5.4 kN
Cracked concrete C20/25	Yes	N _{Rec}	35 mm		1.4 kN
Cracked concrete C20/25	Yes	V _{Rec}	35 mm		5.4 kN
Hollow-core slab, bottom flange thickness 25 mm	Yes	N _{Rec}	35 mm		1.2 kN
Hollow-core slab, bottom flange thickness 25 mm	Yes	V _{Rec}	35 mm		1.2 kN

Installation

