

Concrete Screw S-CSA+ HEX 10X80/25 ML

SORMAT CODE 9640071757



ETA-approved heavy-duty concrete screws for high loads

- Self-tapping, screw anchors for push-through installations.
- Requires a small drill hole diameter. No prescribed tightening torque.
- No expansion forces allowing for small edge distances and spacings.
- Fully removable.
- ML (Multi Layer) corrosion protection coating exceeding 1000 hours in SST acc. ISO 9227.
- For outdoor use in not safety relevant applications.

APPLICATIONS

- Facade scaffoldings
- Temporary fixings
- Seatings
- Shelves
- Cable racks
- Handrails
- Battens

APPROVALS / CERTIFICATES



ETA-20/0446 + DoPs



Fire resistance (ETA-20/0446)

Technical data

INSTALLATION DETAILS

- Jun 6, '21 19:09 18:09:51

PRODUCT OVERVIEW

Other codes	/ LVI 3255585
Material	Multi Layer coated
Packages	box (bag): 25 / outer carton: 125 / pallet: 7000
Weight	61.7 kg / 1000

BASE MATERIALS

APPROVED FOR

- Cracked concrete
- Non-cracked concrete

ALSO SUITABLE FOR

- Solid clay brick
- Solid sand-lime brick




0809-CPR-20006568

INSTALLATION DETAILS

Size	10	Hole in fixture (D_f)	13-14
Length (L)	80	Drill hole diameter (d_0) $\varnothing$	10
Width across flats (SW)	15	Minimum drill hole depth	65
Max. fixture thickness (T_{fix})	25	Drill hole depth (h_1)	65
		Nominal setting depth (H_{nom})	55
		Installation torque (T_{inst})	max 85

HEAD DETAILS

Head diameter $\varnothing$	20,5
-----------------------------	------



Performance data

Base material	Load type	Embedment depth (h_{nom})	Load direction	Load value
All				
Non-cracked concrete C20/25	N_{Rec}	55 mm		6.5 kN
Non-cracked concrete C20/25	V_{Rec}	55 mm		18.2 kN
Cracked concrete C20/25	N_{Rec}	55 mm		3.6 kN
Cracked concrete C20/25	V_{Rec}	55 mm		13.6 kN

Installation

