

Brass anchor MSA 6

SORMAT CODE 9640072206



Quality all-around brass anchors with internal thread

- · Internally threaded brass expansion anchor for preinstallation.
- Cross knurling on the body to prevent rotation during installation.
- Internal thread for metric bolts and rods.
- Brass anchors are suitable for indoor and outdoor use.

PRODUCT OVERVIEW

Other codes SNRO 1356186 / LVI

3252191

Material Brass

Packages box (bag): 100 / outer

carton: 1000 / pallet: 56000

Weight 4.7 kg / 1000

APPLICATIONS

- Air ducts
- Cable trays
- Curtain rails
- Substructures
- Rails
- Protective wall panels
- Safety covers
- Suspended ceilings

BASE MATERIALS

ALSO SUITABLE FOR


- Hollow-core slab
- Natural stone
- Non-cracked concrete
- · Solid clay brick

Technical data

INSTALLATION DETAILS

Length (L)

Size



INSTALLATION DETAILS

Drill hole diameter (d₀) Ø

M6

Nominal setting depth (H_{nom})

24

8

Performance data

Base material	Load type	Embedment depth (h _{nom})	Load direction	Load value
Non-cracked concrete C20/25	N _{Rec}	24 mm		1.0 kN
Non-cracked concrete C20/25	V _{Rec}	24 mm	<u> </u>	1.0 kN

Installation

