

Chemical anchor stud KEVA 24X300 ZP

SORMAT CODE 9640072656



Superior quality sharp-point steel studs for chemical anchoring

- Quality threaded studs equipped with hexagonal grip and 2 x 45° sharp point.
- Used with chemical injection resins and glass capsule anchors, can also be cast-in.
- Delivered with a nut and a washer, sales box includes stud adapter for installation with rotary impact hammer drills.
- ZP for dry indoor and temporary outdoor use.

APPLICATIONS

- Used with chemical resins and capsules

Technical data

INSTALLATION DETAILS

Size	M24
Length (L)	300
Width across flats (SW)	36
Max. fixture thickness (T _{fix})	55
Grip size	13

PRODUCT OVERVIEW

Other codes	/
Material	Steel, zinc plated
Packages	box (bag): 6 / outer carton: 24
Weight	985.0 kg / 1000
GTIN-13	6416031726569

BASE MATERIALS

- ALSO SUITABLE FOR
- Aerated concrete block
 - Hollow light expanded clay aggregate block
 - Hollow-core slab
 - Natural stone
 - Non-cracked concrete
 - Perforated clay brick
 - Solid clay brick
 - Solid light expanded clay aggregate block

INSTALLATION DETAILS

Hole in fixture (D _f)	26
Drill hole diameter (d ₀) Ø	28
Minimum drill hole depth	210
Drill hole depth (h ₁)	210
Nominal setting depth (H _{nom})	210
Effective setting depth (H _{ef})	210