

Chemical anchor stud VKS 10X130 HDG

SORMAT CODE 9640072660



Superior quality sharp-point steel studs for chemical anchoring

- Quality threaded studs equipped with hexagonal grip and 2 x 45° sharp point.
- Used with chemical injection resins and glass capsule anchors, can also be cast-in.
- Delivered with a nut and a washer, sales box includes stud adapter for installation with rotary impact hammer drills.
- HDG for dry and humid indoor use, outdoor in rural areas only.

APPLICATIONS

- Used with chemical resins and capsules

Technical data

INSTALLATION DETAILS

Size	M10
Length (L)	130
Width across flats (SW)	17
Max. fixture thickness (T _{fix})	20
Grip size	7

PRODUCT OVERVIEW

Other codes	/
Material	Steel, hot dip galvanized
Packages	box (bag): 10 / outer carton: 250
Weight	73.0 kg / 1000
GTIN-13	6416031726606

BASE MATERIALS

ALSO SUITABLE FOR

- Aerated concrete block
- Hollow light expanded clay aggregate block
- Hollow-core slab
- Natural stone
- Non-cracked concrete
- Perforated clay brick
- Solid clay brick
- Solid light expanded clay aggregate block

INSTALLATION DETAILS

Hole in fixture (D_f)	12
Drill hole diameter (d₀) ∅	12
Minimum drill hole depth	90
Drill hole depth (h₁)	90
Nominal setting depth (H_{nom})	90
Effective setting depth (H_{ef})	90