

Chemical anchor stud VKS 12X160 HDG

SORMAT CODE 9640072661



Superior quality sharp-point steel studs for chemical anchoring

- Quality threaded studs equipped with hexagonal grip and 2 x 45° sharp point.
- Used with chemical injection resins and glass capsule anchors, can also be cast-in.
- Delivered with a nut and a washer, sales box includes stud adapter for installation with rotary impact hammer drills.
- HDG for dry and humid indoor use, outdoor in rural areas only.

APPLICATIONS

- Used with chemical resins and capsules

Technical data

INSTALLATION DETAILS

Size	M12
Length (L)	160
Width across flats (SW)	19
Max. fixture thickness (T _{fix})	30
Grip size	8

PRODUCT OVERVIEW

Other codes	/
Material	Steel, hot dip galvanized
Packages	box (bag): 10 / outer carton: 150
Weight	133.5 kg / 1000

BASE MATERIALS

- ALSO SUITABLE FOR
- Aerated concrete block
 - Hollow light expanded clay aggregate block
 - Hollow-core slab
 - Natural stone
 - Non-cracked concrete
 - Perforated clay brick
 - Solid clay brick
 - Solid light expanded clay aggregate block

INSTALLATION DETAILS

Hole in fixture (D _f)	14
Drill hole diameter (d ₀) Ø	14
Minimum drill hole depth	110
Drill hole depth (h ₁)	110
Nominal setting depth (H _{nom})	110
Effective setting depth (H _{ef})	110