

Chemical anchor stud VKS 20X260 HDG

SORMAT CODE 9640072664



Superior quality sharp-point steel studs for chemical anchoring

- Quality threaded studs equipped with hexagonal grip and 2 x 45° sharp point.
- Used with chemical injection resins and glass capsule anchors, can also be cast-in.
- Delivered with a nut and a washer, sales box includes stud adapter for installation with rotary impact hammer drills.
- HDG for dry and humid indoor use, outdoor in rural areas only.

APPLICATIONS

- Used with chemical resins and capsules

Technical data

INSTALLATION DETAILS

Size	M20	Hole in fixture (D_f)	22
Length (L)	260	Drill hole diameter (d₀) ø	24
Width across flats (SW)	30	Minimum drill hole depth	170
Max. fixture thickness (T_{fix})	60	Drill hole depth (h₁)	170
Grip size	12	Nominal setting depth (H_{nom})	170
		Effective setting depth (H_{ef})	170

PRODUCT OVERVIEW

Other codes	/
Material	Steel, hot dip galvanized
Packages	box (bag): 6 / outer carton: 30
Weight	571.8 kg / 1000
GTIN-13	6416031726644

BASE MATERIALS

ALSO SUITABLE FOR

- Aerated concrete block
- Hollow light expanded clay aggregate block
- Hollow-core slab
- Natural stone
- Non-cracked concrete
- Perforated clay brick
- Solid clay brick
- Solid light expanded clay aggregate block