


Drop in anchor LAH 12 A4

SORMAT CODE 9640074012



Stainless steel drop in anchors for suspension systems

- Drop in anchors for pre-installation with an installation tool.
- Internal thread for metric bolts and rods.
- Suitable bolt length is 1-1,5 x the nominal size of the anchor + fixture thickness.
- Shallow drilling depth makes drilling and overhead installation easier.
- A4 for indoor, outdoor and industrial use.

APPLICATIONS

- Suspension systems
- Pipelines
- Air ducts
- Sprinkler systems
- Cable trays
- Machines
- Consoles
- Ceiling bearers

Technical data

INSTALLATION DETAILS

Size	M12
Length (L)	50
Thread (f)	24

PRODUCT OVERVIEW


Other codes	SNRO 1355932 / LVI 3252138
Material	Stainless steel, A4
Packages	box (bag): 50 / outer carton: 250 / pallet: 14000
Weight	45.6 kg / 1000
GTIN-13	8716247740129
Availability	end of life

BASE MATERIALS



- ALSO SUITABLE FOR
- Natural stone
 - Non-cracked concrete

INSTALLATION DETAILS

Hole in fixture (D _f)	≤ 14
Drill hole diameter (d ₀) ø	15
Minimum drill hole depth	52
Drill hole depth (h ₁)	52
Nominal setting depth (H _{nom})	50
Effective setting depth (H _{ef})	50
Installation torque (T _{inst})	max 35



Performance data

Base material	Load type	Load direction	Load value
Non-cracked concrete C20/25	N_{Rec}		5.9 kN
Non-cracked concrete C20/25	V_{Rec}		6.3 kN

Installation

