SORMAT 🔁

Drop in anchor LAH 16 A4

SORMAT CODE 9640074016



Stainless steel drop in anchors for suspension systems

- Drop in anchors for pre-installation with an installation tool.
- Internal thread for metric bolts and rods.
- Suitable bolt length is 1-1,5 x the nominal size of the anchor + fixture thickness.
- Shallow drilling depth makes drilling and overhead installation easier.
- A4 for indoor, outdoor and industrial use.

PRODUCT OVERVIEW

Other codes Material Packages Weight GTIN-13 Availability

SNRO 1355936 / Stainless steel, A4 box (bag): 25 / outer carton: 125 / pallet: 7000 96.8 kg / 1000 8716247740167 end of life

APPLICATIONS

- Suspension systems
- Pipelines
- Air ducts
- Sprinkler systems
- Cable trays
- Machines
- Consoles
- · Ceiling bearers

Technical data

INSTALLATION DETAILS

| Size | M16 | Hole in fixture (D _f) | ≤ 18 |
|------------|-----|---|------|
| Length (L) | 65 | Drill hole diameter (d ₀) ø | 20 |
| Thread (f) | 27 | Minimum drill hole depth | 69 |
| | | Drill hole depth (h1) | 69 |

INSTALLATION DETAILS

Nominal setting depth (Hnom)

Effective setting depth (Hef)

Installation torque (Tinst)

Non-cracked concrete

BASE MATERIALS

ALSO SUITABLE FOR

Natural stone


- Sep 18, '23 22:12 21:12:11

1/3

65

65

max 60



Performance data

| Base material | Load type | Load direction | Load value |
|-----------------------------|------------------|----------------|------------|
| Non-cracked concrete C20/25 | N _{Rec} | | 8.8 kN |
| Non-cracked concrete C20/25 | V _{Rec} | * | 11.8 kN |

Installation

