


Drop in anchor LAH 20 A4

SORMAT CODE 9640074020



Stainless steel drop in anchors for suspension systems

- Drop in anchors for pre-installation with an installation tool.
- Internal thread for metric bolts and rods.
- Suitable bolt length is 1-1,5 x the nominal size of the anchor + fixture thickness.
- Shallow drilling depth makes drilling and overhead installation easier.
- A4 for indoor, outdoor and industrial use.

APPLICATIONS

- Suspension systems
- Pipelines
- Air ducts
- Sprinkler systems
- Cable trays
- Machines
- Consoles
- Ceiling bearers

Technical data

INSTALLATION DETAILS

Size	M20
Length (L)	80
Thread (f)	36

PRODUCT OVERVIEW


Other codes	SNRO 1355940 /
Material	Stainless steel, A4
Packages	box (bag): 20 / outer carton: 100 / pallet: 5600
Weight	199.7 kg / 1000
GTIN-13	6416031740206
Availability	end of life

BASE MATERIALS

- ALSO SUITABLE FOR
- Natural stone
 - Non-cracked concrete

INSTALLATION DETAILS

Hole in fixture (D_f)	≤ 22
Drill hole diameter (d_0) \varnothing	25
Minimum drill hole depth	84
Drill hole depth (h_1)	84
Nominal setting depth (H_{nom})	80
Effective setting depth (H_{ef})	80
Installation torque (T_{inst})	max 100



Performance data

Base material	Load type	Load direction	Load value
Non-cracked concrete C20/25	N_{Rec}		12.0 kN
Non-cracked concrete C20/25	V_{Rec}		18.4 kN

Installation

