


Universal plastic plug YLT 10 PE

SORMAT CODE 9640075212



Economival universal plug that tightens into a tough knot

- Universal polyethylene plug with collar for pre-installation in all types of base materials.
- Due to knotting YLT can be used in most base materials.
- Collar prevents the plug from slipping into the drill hole.
- Suitable for wood and chipboard screws.
- Suitable conditions related to screw material: ZP for dry indoor and temporary outdoor use; HGD/MG and A2 for dry and humid indoor use, outdoor in rural areas only; A4 for indoor, outdoor and industrial use.

APPLICATIONS

- Wall-mounted cabinets
- Shelves
- Curtain rails
- TV consoles
- Electrical installations
- HVAC and plumbing fixings
- Sanitary fixings

Technical data

INSTALLATION DETAILS

Size	10
Length (L)	56
Suitable screws Diameter	6,0 - 7,0
Suitable screws Length	56 + tfix + 5

PRODUCT OVERVIEW

Other codes	SNRO 1350430 /
Material	Polyethylene
Packages	box (bag): 50 / outer carton: 1000
Weight	2.8 kg / 1000

BASE MATERIALS

- ALSO SUITABLE FOR
- Gypsum plasterboard
 - Gypsum plasterboard composite
 - Natural stone
 - Non-cracked concrete
 - Perforated clay brick
 - Perforated sand-lime brick
 - Solid clay brick
 - Solid sand-lime brick
 - Timber-based building boards

INSTALLATION DETAILS

Drill hole diameter (d ₀) Ø	10
---	----

Performance data

Base material	Load type	Load direction	Load value
All			
Non-cracked concrete C20/25	N _{Rec}		0.50 kN
Gypsum board composite, thickness 12,5 mm	N _{Rec}		0.25 kN

Installation

