

# Nail plug LIT 5/35 with brown nail

SORMAT CODE 9640075641



## For quick fixing of baseboards and covering strips in concrete and masonry

- Ready-to-install nylon plug for hammer-in -type through fixings.
- It is recommended to use a nylon hammer when installing.
- Nailscrew head with pozidrive slot for removing or adjusting the anchor.
- Head of the nailscrew covers the head of the plug which will be invisible to the eye.
- White and brown plugs available. Supplied with preassembled nails in various colours.
- ZP for dry indoor and temporary outdoor use.

## APPLICATIONS

- Baseboards
- Covering strips

## Technical data

### INSTALLATION DETAILS

Length (L)  
Max. fixture thickness (T<sub>fix</sub>)

35  
5

### PRODUCT OVERVIEW


Other codes	SNRO 1308851 /
Material	Polyamide / Steel, zinc plated
Packages	box (bag): 200 / outer carton: 2000 / pallet: 56000
Weight	3.0 kg / 1000

### BASE MATERIALS

- ALSO SUITABLE FOR
- Natural stone
  - Non-cracked concrete
  - Perforated clay brick
  - Solid clay brick

### INSTALLATION DETAILS

Drill hole diameter (d <sub>0</sub> ) Ø	5
Minimum drill hole depth	35
Drill hole depth (h <sub>1</sub> )	35
Total drilling depth	40
Nominal setting depth (H <sub>nom</sub> )	30



## Installation

---

