

Molly building board anchor MOLA 4/13 ZP

SORMAT CODE 9640075702



Full metal Molly for strong anchoring in board and hollow walls

- Molly-type all-metal anchor with arms that expand onto the reverse side of the board for strong grip.
- MOLA is suitable for fixing heavier in accordance with the board material properties.
- Suitable for sheet thicknesses 6-26 mm, requires a hollow cavity behind the sheet. Possible wall insulation material may complicate the installation.
- Use in applications where fire resistance is required.
- The fixture can be removed and refitted by loosening the screw.
- Tighten the anchor using special MOLA assembly pliers.
- ZP for dry indoor and temporary outdoor use.

APPLICATIONS

- Wall-mounted cabinets
- Storage shelves
- Book shelves
- TV mounts
- Radiators
- Wash basins
- Electrical installations
- HVAC and plumbing fixings
- Sanitary fixings

Technical data

INSTALLATION DETAILS

Max. fixture thickness (T _{fix})	9
Min. sheet thickness (T _{sheet, min})	8
Max. sheet thickness (T _{sheet, max})	13
Free space behind the sheet	29
Suitable screws Diameter	M4 x 41

PRODUCT OVERVIEW

Properties	with screw M4 x 41 mm
Other codes	SNRO 1357032 /
Material	Steel, zinc plated
Packages	box (bag): 50 / outer carton: 500 / pallet: 38000
Weight	7.2 kg / 1000
GTIN-13	6416031757020

BASE MATERIALS

- ALSO SUITABLE FOR
- Gypsum plasterboard
 - Gypsum plasterboard composite
 - Timber-based building boards

INSTALLATION DETAILS

Drill hole diameter (d ₀) Ø	8
---	---

Performance data

Base material	Load type	Load direction	Load value
All			
Gypsum board standard, thickness 12,5 mm	N _{Rec}		0.15 kN
Gypsum board composite, thickness 12,5 mm	N _{Rec}		0.20 kN
Gypsum board standard, thickness 12,5 mm	V _{Rec}		0.15 kN
Gypsum board composite, thickness 12,5 mm	V _{Rec}		0.20 kN

Installation

