

Molly building board anc MOLA 6/13 ZP

SORMAT CODE

9640075710



Full metal Molly for strong anchoring in board and hollow walls

- Molly-type all-metal anchor with arms that expand onto the reverse side of the board for strong grip.
- MOLA is suitable for fixing heavier in accordance with the board material properties.
- Suitable for sheet thicknesses 6-26 mm, requires a hollow cavity behind the sheet. Possible wall insulation material may complicate the installation.
- Use in applications where fire resistance is required.
- The fixture can be removed and refitted by loosening the screw.
- Tighten the anchor with a screw driver or, with hard base materials like plywood, use special MOLA assembly pliers.
- ZP for dry indoor and temporary outdoor use.

APPLICATIONS

- Wall-mounted cabinets
- Storage shelves
- Book shelves
- TV mounts
- Radiators
- Wash basins
- Electrical installations
- HVAC and plumbing fixings
- Sanitary fixings

Technical data

INSTALLATION DETAILS

Max. fixture thickness (T _{fix})	13
Min. sheet thickness (T _{sheet, min})	8
Max. sheet thickness (T _{sheet, max})	13
Free space behind the sheet	32

PRODUCT OVERVIEW

Properties	with screw M6 x 45 mm
Other codes	SNRO 1357046 /
Material	Steel, zinc plated
Packages	box (bag): 50 / outer carton: 500 / pallet: 24000
Weight	16.9 kg / 1000

BASE MATERIALS

- ALSO SUITABLE FOR
- Gypsum plasterboard
 - Gypsum plasterboard composite
 - Timber-based building boards

INSTALLATION DETAILS

Drill hole diameter (d ₀) Ø	12
---	----

Performance data

Base material	Load type	Load direction	Load value
All			
Gypsum board standard, thickness 12,5 mm	N _{Rec}		0.15 kN
Gypsum board composite, thickness 12,5 mm	N _{Rec}		0.25 kN

Installation

