

Plasterboard fixing KLA met+Screw

SORMAT CODE 9640075920



Self-drilling metallic quickie for fixing into gypsum plasterboard walls

- Fire-proof self-drilling anchor for standard and composite gypsum plasterboard walls and gypsum fibreboard walls.
- Predrill with a 8 mm drill bit when fixing to gypsum fibreboard and double-planked gypsum plasterboard.
- The quickest way to fix light objects. No special tools needed, just a PZ2 screwdriver. Set flush with the board surface, do not overtighten.
- Equipped with a 4,5 x 35 mm ZP screw. Can also be used with other suitable wood- and self-tapping and chipboard screws, hookscrews and eyescrews.
- ZP for dry indoor and temporary outdoor use.

APPLICATIONS

- Pictures
- Paintings
- Lighting
- Coat hangers
- Electrical installations

Technical data

INSTALLATION DETAILS

| | |
|---|----------|
| Length (L) | 31 |
| Max. fixture thickness (T _{fix}) | 12 |
| Min. sheet thickness (T _{sheet, min}) | 9 |
| Max. sheet thickness (T _{sheet, max}) | - |
| Free space behind the sheet | 19 |
| Suitable screws Diameter | 4,5 x 35 |

PRODUCT OVERVIEW

| | |
|-------------|--|
| Other codes | SNRO 1357080 / LVI 3253375 |
| Material | Zinc die casted |
| Packages | box (bag): 100 / outer carton: 1000 / pallet: 24000 |
| Weight | 6.3 kg / 1000 |

BASE MATERIALS



ALSO SUITABLE FOR

- Gypsum plasterboard
- Gypsum plasterboard composite

INSTALLATION DETAILS

| | |
|---|---|
| Drill hole diameter (d ₀) Ø | - |
|---|---|

Performance data

| Base material | Load type | Load direction | Load value |
|---|------------------|---|------------|
| All | | | |
| Gypsum board standard, thickness 12,5 mm | N _{Rec} |  | 0.08 kN |
| Gypsum board composite, thickness 12,5 mm | N _{Rec} |  | 0.08 kN |

Installation

