

Plasterboard fixing KLA nylon+Screw

SORMAT CODE 9640075921



Self-drilling quickie for fixing into gypsum plasterboard walls

- Self-drilling nylon anchor for standard gypsum plasterboard walls.
- The quickest way to fix light objects. No special tools needed, just a PZ2 screwdriver. Set flush with the board surface, do not overtighten.
- Equipped with a 4,5 x 35 mm ZP screw. Can also be used with other suitable wood- and self-tapping and chipboard screws, hookscrews and eyescrews.
- Suitable conditions related to screw material: ZP for dry indoor and temporary outdoor use; HGD/MG and A2 for dry and humid indoor use, outdoor in rural areas only; A4 for indoor, outdoor and industrial use.

APPLICATIONS

- Pictures
- Paintings
- Lighting
- Coat hangers
- Electrical installations

Technical data

INSTALLATION DETAILS

| | |
|---|----------|
| Length (L) | 37 |
| Max. fixture thickness (T _{fix}) | 12 |
| Min. sheet thickness (T _{sheet, min}) | 9 |
| Max. sheet thickness (T _{sheet, max}) | 13 |
| Free space behind the sheet | 24 |
| Suitable screws Diameter | 4,5 x 35 |

PRODUCT OVERVIEW

| | |
|-------------|--|
| Other codes | SNRO 1357082 / LVI 3253372 |
| Material | Polyamide |
| Packages | box (bag): 100 / outer carton: 1000 / pallet: 24000 |
| Weight | 4.0 kg / 1000 |

BASE MATERIALS

- ALSO SUITABLE FOR
- Gypsum plasterboard

INSTALLATION DETAILS

| | |
|---|---|
| Drill hole diameter (d ₀) Ø | - |
|---|---|

Performance data

| Base material | Load type | Load direction | Load value |
|--|------------------|---|------------|
| Gypsum board standard, thickness 12,5 mm | N _{Rec} |  | 0.08 kN |

Installation

