

Through bolt S-KAK+ 8/63/50 HDG (3 DIY)

SORMAT CODE 9640094113



Improved premium-quality hdg through bolts for fixing in non-cracked and cracked concrete

- Torque-controlled expansion anchors for pre-, push-through and distance installations.
- When torque is applied the expansion clip expands developing frictional grip with the drill hole walls.
- Anchor diameter and max. fixture thicknesses marked on the body. Anchor length letter code marked on the bolt head.
- M8, M10 and M12 have two different anchorage depths.
- The use of S-KA setting tool makes serial installation safer and quicker.
- HDG for dry and humid indoor use, outdoor inland rural areas only.

PRODUCT OVERVIEW

Other codes	/
Material	Steel, hot dip galvanized
Packages	box (bag): 3 / outer carton: 30
Weight	43.5 kg / 1000
GTIN-13	6416031941139

APPLICATIONS

- Steel structures
- Column base plates
- Seatings
- Barriers
- Cable racks
- Handrails
- Ladders
- Façade systems

BASE MATERIALS

APPROVED FOR

- Cracked concrete
- Non-cracked concrete

ALSO SUITABLE FOR

- Natural stone

APPROVALS / CERTIFICATES



ETA-16/0934 + DoPs



0809-CPR-1252




Fire resistance (ETA-16/0934)

Technical data

INSTALLATION DETAILS

Size
Length (L)
Thread (f)
Width across flats (SW)
Max. fixture thickness (T _{fix})



INSTALLATION DETAILS

M8	Hole in fixture (D _f)	9
115	Drill hole diameter (d ₀) ∅	8
75	Minimum drill hole depth	47/60
13	Drill hole depth (h ₁)	47/60
63/50	Nominal setting depth (H _{nom})	40/53
	Effective setting depth (H _{ef})	35/48
	Installation torque (T _{inst})	15

Installation

