

# Through bolt S-KAH+ 10/30/10 A4 (2 DIY)

SORMAT CODE 9640094219



## Improved premium-quality A4 through bolts for fixing in non-cracked and cracked concrete

- Torque-controlled expansion anchors for pre-, push-through and distance installations.
- When torque is applied the expansion clip expands developing frictional grip with the drill hole walls.
- Anchor diameter and max. fixture thicknesses marked on the body. Anchor length letter code marked on the bolt head.
- M8, M10 and M12 have two different anchorage depths.
- The use of S-KA setting tool makes serial installation safer and quicker.
- Seismic performance category C1/C2 ( $h_{ef, std}$ ).
- A4 for indoor, outdoor and industrial use.

## PRODUCT OVERVIEW

<b>Other codes</b>	/
<b>Material</b>	Stainless steel, A4
<b>Packages</b>	box (bag): 2 / outer carton: 20
<b>Weight</b>	59.7 kg / 1000
<b>GTIN-13</b>	6416031942198

## APPLICATIONS

- Steel structures
- Column base plates
- Seatings
- Barriers
- Cable racks
- Handrails
- Ladders
- Façade systems

## BASE MATERIALS

### APPROVED FOR

- Cracked concrete
- Non-cracked concrete

### ALSO SUITABLE FOR

- Natural stone

## APPROVALS / CERTIFICATES



ETA-16/0934 + DoPs



Fire resistance (ETA-16/0934)



0809-CPR-1252




Seismic resistance (ETA-16/0934)

# Technical data

## INSTALLATION DETAILS

Size
Length (L)
Thread (f)
Width across flats (SW)
Max. fixture thickness (T <sub>fix</sub> )



## INSTALLATION DETAILS

M10	Hole in fixture (D <sub>f</sub> )	12
92	Drill hole diameter (d <sub>0</sub> ) ∅	10
47	Minimum drill hole depth	55/75
17	Drill hole depth (h <sub>1</sub> )	55/75
30/10	Nominal setting depth (H <sub>nom</sub> )	48/68
	Effective setting depth (H <sub>ef</sub> )	40/60
	Installation torque (T <sub>inst</sub> )	45

## Installation

