

Through bolt S-KAH+ 10/40/20 A4 (2 DIY)

SORMAT CODE 9640094221



Improved premium-quality A4 through bolts for fixing in non-cracked and cracked concrete

- Torque-controlled expansion anchors for pre-, push-through and distance installations.
- When torque is applied the expansion clip expands developing frictional grip with the drill hole walls.
- Anchor diameter and max. fixture thicknesses marked on the body. Anchor length letter code marked on the bolt head.
- M8, M10 and M12 have two different anchorage depths.
- The use of S-KA setting tool makes serial installation safer and quicker.
- Seismic performance category C1/C2 (h_{ef,std}).
- A4 for indoor, outdoor and industrial use.

PRODUCT OVERVIEW

Other codes

Material Packages Weight

GTIN-13

Stainless steel, A4 box (bag): 2 / outer carton: 20 65.0 kg / 1000

6416031942211

APPLICATIONS

- Steel structures
- · Column base plates
- Seatings
- Barriers
- Cable racks
- Handrails
- Ladders
- · Façade systems

BASE MATERIALS

APPROVED FOR

- · Cracked concrete
- Non-cracked concrete

ALSO SUITABLE FOR

Natural stone

APPROVALS / CERTIFICATES



ETA-16/0934 + DoPs



Fire resistance (ETA-16/0934)



0809-CPR-1252



Seismic resistance (ETA-16/0934)

Technical data

INSTALLATION DETAILS

Size Length (L) Thread (f) Width across flats (SW) 17 Max. fixture thickness (T_{fix}) 40/20

h,

INSTALLATION DETAILS

Hole in fixture (D _f)	12
Drill hole diameter (d₀) Ø	10
Minimum drill hole depth	55/75
Drill hole depth (h ₁)	55/75
Nominal setting depth (H _{nom})	48/68
Effective setting depth (H _{ef})	40/60
Installation torque (T _{inst})	45

Installation

