

Plasterboard fixing KLA nylon (10 DIY)

SORMAT CODE 9640095600



Self-drilling quickie for fixing into gypsum plasterboard walls

- Self-drilling nylon anchor for standard gypsum plasterboard walls.
- The quickest way to fix light objects. No special tools needed, just a PZ2 screwdriver. Set flush with the board surface, do not overtighten.
- Equipped with a 4,5 x 35 mm ZP screw. Can also be used with other suitable wood- and self-tapping and chipboard screws, hookscrews and eyescrews.
- Suitable conditions related to screw material: ZP for dry indoor and temporary outdoor use; HGD/MG and A2 for dry and humid indoor use, outdoor in rural areas only; A4 for indoor, outdoor and industrial use.

PRODUCT OVERVIEW

Other codes	SNRO 1372068 /
Material	Polyamide
Packages	box (bag): 10 / outer carton: 100 / piece: 1
Weight	4.0 kg / 1000

APPLICATIONS

- Pictures
- Paintings
- Lighting
- Coat hangers
- Electrical installations

BASE MATERIALS

- ALSO SUITABLE FOR
- Gypsum plasterboard

Technical data

INSTALLATION DETAILS

Length (L)	37
Max. fixture thickness (T_{fix})	12
Min. sheet thickness (T_{sheet, min})	9
Max. sheet thickness (T_{sheet, max})	13
Free space behind the sheet	24
Suitable screws Diameter	4,5 x 35

Performance data

Base material	Load type	Load direction	Load value
Gypsum board standard, thickness 12,5 mm	N _{Rec}		0.08 kN

Installation

