

# Molly building board anc MOLA 5/13 (5DIY)

SORMAT CODE 

9640095622



## Full metal Molly for strong anchoring in board and hollow walls

- Molly-type all-metal anchor with arms that expand onto the reverse side of the board for strong grip.
- MOLA is suitable for fixing heavier in accordance with the board material properties.
- Suitable for sheet thicknesses 6-26 mm, requires a hollow cavity behind the sheet. Possible wall insulation material may complicate the installation.
- Use in applications where fire resistance is required.
- The fixture can be removed and refitted by loosening the screw.
- Tighten the anchor with a screw driver or, with hard base materials like plywood, use special MOLA assembly pliers.
- ZP for dry indoor and temporary outdoor use.

## APPLICATIONS

- Wall-mounted cabinets
- Storage shelves
- Book shelves
- TV mounts
- Radiators
- Wash basins
- Electrical installations
- HVAC and plumbing fixings
- Sanitary fixings

## Technical data

### INSTALLATION DETAILS

Max. fixture thickness (T <sub>fix</sub> )	13
Min. sheet thickness (T <sub>sheet, min</sub> )	8
Max. sheet thickness (T <sub>sheet, max</sub> )	13
Free space behind the sheet	32

### PRODUCT OVERVIEW

Properties	with screw M5 x 45 mm
Other codes	SNRO 1372071 /
Material	Steel, zinc plated
Packages	box (bag): 5 / outer carton: 50 / piece: 1
Weight	12.0 kg / 1000

### BASE MATERIALS


- ALSO SUITABLE FOR
- Gypsum plasterboard
  - Gypsum plasterboard composite
  - Timber-based building boards

### INSTALLATION DETAILS

Drill hole diameter (d <sub>0</sub> ) Ø	10
---	----



# Performance data

Base material	Load type	Load direction	Load value
All			
Gypsum board standard, thickness 12,5 mm	N <sub>Rec</sub>		0.15 kN
Gypsum board composite, thickness 12,5 mm	N <sub>Rec</sub>		0.25 kN

# Installation

