

Molly building board anc MOLA 6/26 (5DIY)

SORMAT CODE 9640095628



Full metal Molly for strong anchoring in board and hollow walls

- Molly-type all-metal anchor with arms that expand onto the reverse side of the board for strong grip.
- MOLA is suitable for fixing heavier in accordance with the board material properties.
- Suitable for sheet thicknesses 6-26 mm, requires a hollow cavity behind the sheet. Possible wall insulation material may complicate the installation.
- Use in applications where fire resistance is required.
- The fixture can be removed and refitted by loosening the screw.
- Tighten the anchor with a screw driver or, with hard base materials like plywood, use special MOLA assembly pliers.
- ZP for dry indoor and temporary outdoor use.

APPLICATIONS

- Wall-mounted cabinets
- Storage shelves
- Book shelves
- TV mounts
- Radiators
- Wash basins
- Electrical installations
- HVAC and plumbing fixings
- Sanitary fixings

Technical data

INSTALLATION DETAILS

Max. fixture thickness (T _{fix})	21
Min. sheet thickness (T _{sheet, min})	20
Max. sheet thickness (T _{sheet, max})	26
Free space behind the sheet	46

PRODUCT OVERVIEW

Properties	with screw M6 x 72 mm
Other codes	SNRO 1372074 /
Material	Steel, zinc plated
Packages	box (bag): 5 / outer carton: 50 / piece: 1
Weight	25.4 kg / 1000

BASE MATERIALS

- ALSO SUITABLE FOR
- Gypsum plasterboard
 - Gypsum plasterboard composite
 - Timber-based building boards

INSTALLATION DETAILS

Drill hole diameter (d ₀) Ø	12
---	----

Performance data

Base material	Load type	Load direction	Load value
Gypsum board composite double, thickness 2 x 12,5 mm	N _{Rec}		0.40 kN

Installation

