

# Universal plast Plug YLT 8 (10 DIY)

SORMAT CODE 9640095652



## Economival universal plug that tightens into a tough knot

- Universal polyethylene plug with collar for pre-installation in all types of base materials.
- Due to knotting YLT can be used in most base materials.
- Collar prevents the plug from slipping into the drill hole.
- Suitable for wood and chipboard screws.
- Suitable conditions related to screw material: ZP for dry indoor and temporary outdoor use; HGD/MG and A2 for dry and humid indoor use, outdoor in rural areas only; A4 for indoor, outdoor and industrial use.

## APPLICATIONS

- Wall-mounted cabinets
- Shelves
- Curtain rails
- TV consoles
- Electrical installations
- HVAC and plumbing fixings
- Sanitary fixings

## Technical data

### INSTALLATION DETAILS

Size	8
Length (L)	48
Suitable screws Diameter	3,5 - 6,0

## PRODUCT OVERVIEW

Other codes	SNRO 1372058 /
Material	Polyethylene
Packages	box (bag): 10 / outer carton: 100 / piece: 1
Weight	1.6 kg / 1000

## BASE MATERIALS

- ALSO SUITABLE FOR
- Gypsum plasterboard
  - Gypsum plasterboard composite
  - Natural stone
  - Non-cracked concrete
  - Perforated clay block
  - Perforated sand-lime brick
  - Solid clay brick
  - Solid sand-lime brick
  - Timber-based building boards

### INSTALLATION DETAILS

Drill hole diameter (d <sub>0</sub> ) Ø	8
---	---

# Performance data

Base material	Load type	Load direction	Load value
All			
Non-cracked concrete C20/25	N <sub>Rec</sub>		0.50 kN
Gypsum board composite, thickness 12,5 mm	N <sub>Rec</sub>		0.20 kN

## Installation

