

Concrete Screw S-CSA HEX 5X40 ZP (10 DIY)

SORMAT CODE 9640095930



ETA-approved 6/8/10 concrete screw for cracked and non-cracked concrete

- Self-tapping screw anchors for push-through installations.
- Requires a small drill hole diameter. No prescribed tightening torque.
- No expansion forces allowing for small edge distances and spacings.
- Fully removable.
- ZP for dry indoor use.

APPLICATIONS

- Facade scaffoldings
- Temporary fixings
- Seatings
- Shelves
- Cable racks
- Handrails
- Battens

PRODUCT OVERVIEW

Other codes	SNRO 1310096 /
Material	Steel, zinc plated
Packages	box (bag): 10 / outer carton: 100
Weight	7.9 kg / 1000

BASE MATERIALS

- ALSO SUITABLE FOR
- Hollow-core slab
 - Non-cracked concrete
 - Solid clay brick
 - Solid sand-lime brick

APPROVALS / CERTIFICATES



TC 5905-19


Technical data

INSTALLATION DETAILS

Size	5
Length (L)	40
Thread (f)	40
Width across flats (SW)	8
Max. fixture thickness (T _{fix})	5

INSTALLATION DETAILS

Hole in fixture (D _f)	7
Drill hole diameter (d ₀) Ø	5
Minimum drill hole depth	45
Drill hole depth (h ₁)	45
Nominal setting depth (H _{nom})	35



Installation torque (T_{inst})



12

HEAD DETAILS

Head diameter \varnothing

11,5

Performance data

Base material	ETA	Load type	Embedment depth (h _{nom})	Load direction	Load value
Non-cracked concrete C20/25	No	N _{Rec}	35 mm		1.1 kN
Non-cracked concrete C20/25	No	V _{Rec}	35 mm		1.1 kN

Installation

