

Liebig Superplus BLS M16-25/200/40 ZP

SORMAT CODE 9655200040



Simply the best heavy duty self-undercutting anchor in the world

- Automatically self-undercutting, unique heavy duty anchor for push-through installations.
- Simplest, quickest and safest solution on the market.
- Economical: No special drill bits, undercut tools or setting tools.
- Minimal expansion forces allow for small spacings and edge distances.
- ZP for dry indoor and temporary outdoor use.

PRODUCT OVERVIEW

Other codes	/
Material	Steel, zinc plated
Packages	box (bag): 5 / outer carton: 20
Weight	890.0 kg / 1000

APPLICATIONS

- Steel structures
- Machines
- Guardrails
- Car lifting systems
- Railings
- Base plates
- Warehouse racks
- Close edge distances
- Small anchor spacings

BASE MATERIALS

APPROVED FOR

- Cracked concrete
- Non-cracked concrete

APPROVALS / CERTIFICATES



ETA-01/0011 + DoPs



Fire resistance (ETA-01/0011)



0809-CPR-19006295




Seismic resistance (ETA-01/0011)

Technical data

INSTALLATION DETAILS

INSTALLATION DETAILS

Size	M16	Hole in fixture (D_f)	26
Length (L)	280	Drill hole diameter (d_0) $\varnothing$	25
Width across flats (SW)	24	Minimum drill hole depth	235
Max. fixture thickness (T_{fix})	40	Drill hole depth (h_1)	235
		Nominal setting depth (H_{nom})	218
		Effective setting depth (H_{ef})	200
		Installation torque (T_{inst})	180



Performance data

Base material	Load type	Embedment depth (h_{nom})	Load direction	Load value
All				
Non-cracked concrete C20/25	N_{Rec}	218 mm		59.8 kN
Non-cracked concrete C20/25	V_{Rec}	218 mm		67.4 kN
Cracked concrete C20/25	N_{Rec}	218 mm		35.7 kN
Cracked concrete C20/25	V_{Rec}	218 mm		67.4 kN

Installation

